

NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS STATED OTHERWISE.
- 2. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH HST/1100/002.
- 3. THIS DRAWING SHALL BE READ IN CONJUNCTION WITH HST/1100/043.
- 4. REFER TO THE WORKS ORDER FOR PRECAST CONCRETE HIGH RELIEF PAVING AND CLAY BLOCK PAVERS SIZES/DIMENSIONS, COLOUR AND FINISH.
- 5. CLAY BLOCK PAVERS SHALL COMPLY WITH BS 6677 PART 1
- ALL JOINTS TO BE LESS THAN 10mm AND POINTED WITH A SAND/CEMENT GROUT.
- 7. VIBRATING PLATE COMPACTORS SHALL CONFORM TO THE REQUIREMENTS OF CLAUSE 6.9.4 OF BS 7533.4.
- 8. MORTAR SHALL BE DESIGNATION (ii) OR (iii). CLAUSE 2404 AS PER SPECIFICATION OF HIGHWAY WORKS.
- 9. ALL MORTAR POINTING SHALL BE COLOUR MATCHED TO THE FLAG.
- 10. MORTAR PIGMENT SHALL COMPLY WITH BS 1014.
- 11. SUBBASE SHALL BE ONE OF THE MATERIALS COMPLYING WITH CLAUSE 803 OR CLAUSE 891AR, 892AR, 893AR OR 894AR, AS SPECIFIED IN THE WORKS INFORMATION.
- 12. WHEN EXCAVATING TO FOOTWAY FORMATION LEVEL THE FULL DEPTH OF EXISTING MATERIAL, INCLUDING TOPSOIL SHALL BE REMOVED, ANY ADDITIONAL DEPTH OF EXCAVATION RESULTING FROM THIS SHALL BE BACKFILLED WITH SUBBASE AS NOTE 11.



COUNTY HALL Pegs Lane Hertford, Herts SG13 8DN Phone: 01992 555555

Revisions

A -FEB 20 REVISED DETAIL

B **-**

C-

Drawing Title

FOOTWAY TYPE 15 PEDESTRIAN DETERRENT PAVING

Dwg No:	HST/1100/049		
Scale at A4 : 1:10		0	
Drawn		Approved	Revised
YS		·· HH	A
Checked		Date	Date
KK		JULY 11	FEB 20